


# Komercinės serijos kondicionieriai



## ORTAKINIAI KONDICIONIERIAI

Modelis	Vidinis		RCDY18AR32	RCDY24AR32	RCDY36AR32	RCDY48AR32	RCDY60AR32
	Išorinis		RCOY18AR32	RCOY24AR32	RCOY36AR32	RCOY48FR32	RCOY60FR32
Galia	Šaldymas	kW	5,3 (2,0 - 5,6)	7,0 (3,5 - 8,0)	10,5 (6,6 - 12,8)	14,0 (7,15 - 15,6)	16,0 (7,8 - 17,5)
	Šildymas	kW	5,9 (3,0 - 6,0)	7,7 (4,5 - 8,5)	11,5 (7,35 - 13,2)	15,2 (8,0 - 17,2)	17,6 (8,5 - 19,5)
SEER/SCOP			6,1 / 4,0	6,1 / 4,0	6,1 / 4,0	6,1 / 4,0	6,1 / 4,0
Energijos klasė			A++ / A+	A++ / A+	A++ / A+	A++ / A+	A++ / A+
Maitinimo įtampa		F,V,Hz	1F,220~240V, 50Hz	1F,220~240V, 50Hz	1F,220~240V, 50Hz	3F,380~415V, 50Hz	3F,380~415V, 50Hz
El. galia	Šaldymas	kW	1,59 (0,42 - 2,10)	2,15 (0,60 - 3,00)	3,28 (0,74 - 4,60)	4,78 (1,22 - 5,70)	5,33 (1,90 - 6,70)
	Šildymas	kW	1,47 (0,50 - 1,94)	1,93 (1,50 - 2,60)	3,20 (1,10 - 4,15)	4,70 (1,20 - 5,50)	5,60 (2,00 - 6,50)
El. srovė	Šaldymas	A	6,9 (1,8-9,1)	9,3 (2,8-13,3)	14,8 (3,1-25,3)	2,5-13	3-14,5
	Šildymas	A	5,5-9,2	5,8-11,3	15,3 (4,5-22)	3-13,5	43539,00
<b>Vidinis</b>							
Išoriniai matmenys	H x W x D	mm	210 x 1214 x 467	210 x 1214 x 467	260 x 1425 x 643	307 x 1279 x 830	307 x 1279 x 830
Pakavimo matmenys	H x W x D	mm	240 x 1310 x 510	240 x 1310 x 510	325 x 1490 x 720	380 x 1395 x 920	380 x 1395 x 920
Neto svoris/ Bruto svoris		kg	22,5 / 25,5	25,0 / 28,0	46,0 / 50,0	49,0 / 56,0	49,0 / 56,0
Triukšmo lygis		dB	45 / 40 / 36	47 / 45 / 43	48 / 46 / 42	47 / 42	47 / 42
Oro srautas		m³/h	800 / 630 / 530	800 / 630 / 530	1800 / 1500 / 1200	2000 / 1800 / 1600	2000 / 1800 / 1600
Išorinis statinis slėgis	Nominalus	Pa	0 - 30	0 - 30	30 - 50	120	120
<b>Išorinis</b>							
Išoriniai matmenys	H x W x D	mm	925 x 700 x 366	958 x 843 x 392	1050 x 995 x 347	1335 x 950 x 388	1335 x 950 x 388
Pakavimo matmenys	H x W x D	mm	990 x 770 x 410	1025 x 960 x 430	1145 x 1120 x 475	1445 x 964 x 402	1445 x 964 x 402
Neto svoris/ Bruto svoris		kg	45,0 / 48,0	59,0 / 69,0	84,0 / 95,5	124,0 / 138,0	124,0 / 138,0
Triukšmo lygis		dB	52	54	55	58	58
Šaltnešio kiekis		kg	1,30	1,70	2,15	3,80	3,80
Veikimo temperatūros	šaldymo/ šildymo	°C	-15~+50/ -15~+30	-15~+50/ -15~+30	-15~+50/ -15~+30	-15~+50/ -15~+30	-15~+50/ -15~+30
Vamzdelių skersmuo	dujos	mm (in)	12,7 (1/2)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)
	skystis	mm (in)	6,35 (1/4)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)
Vamzdelių maks. trasa	aukštis/ilgis	m	8 / 15	10 / 20	30 / 65	30 / 65	30 / 65
Elektros instaliacija	Maitinimo priedimas		Išorinis	Išorinis	Išorinis	Išorinis	Išorinis
	Maitinimo kabelis		3 x 2,5	3 x 2,5	3 x 4,0	5 x 2,5	5 x 2,5
	Tarpblokis k.		4 x 2,5	4 x 2,5	3 x 1,0	3 x 1,0	3 x 1,0



## KASETINIAI KONDICIONIERIAI

Modelis	Vidinis		RCKY18AR32	RCKY24AR32	RCKY36AR32	RCKY48AR32	RCKY60AR32
	Išorinis		RCOY18AR32	RCOY24AR32	RCOY36AR32	RCOY48FR32	RCOY60FR32
	Dekoratyvinė panelė		RCKPYB32	RCKPYB32	RCKPYB32	RCKPYB32	RCKPYB32
Galia	Šaldymas	kW	5,3 (2,0 - 5,6)	7,0 (3,5 - 8,0)	10,5 (6,6 - 12,8)	14,0 (7,1 - 15,6)	16,0 (7,8 - 17,5)
	Šildymas	kW	5,9 (3,0 - 6,0)	7,7 (4,5 - 8,5)	11,5 (7,35 - 13,2)	15,2 (8,0 - 17,2)	17,6 (8,5 - 19,5)
SEER/SCOP			6,1 / 4,0	6,1 / 4,0	6,1 / 4,0	6,1 / 4,0	6,1 / 4,0
Energijos klasė			A++ / A+	A++ / A+	A++ / A+	A++ / A+	A++ / A+
Maitinimo įtampa		F,V,Hz	1F,220~240V, 50Hz	1F,220~240V, 50Hz	1F,220~240V, 50Hz	3F,380~415V, 50Hz	3F,380~415V, 50Hz
El. galia	Šaldymas	kW	1,59 (0,42 - 2,10)	2,15 (0,60 - 3,00)	3,28 (0,74 - 4,60)	4,78 (1,22 - 5,70)	5,33 (1,90 - 6,70)
	Šildymas	kW	1,47 (0,50 - 1,94)	1,93 (1,50 - 2,60)	3,20 (1,10 - 4,15)	4,70 (1,20 - 5,50)	5,60 (2,00 - 6,50)
El. srovė	Šaldymas	A	2,10 - 10,00	2,50 - 13,00	13,60 (2,80 - 24,80)	14,00 (3,00 - 14,50)	16,00 (3,00 - 17,00)
	Šildymas	A	2,50 - 9,20	5,50 - 11,00	14,70 (4,20 - 21,40)	12,00 (2,00 - 14,00)	14,00 (2,00 - 16,00)
<b>Vidinis</b>							
Išoriniai matmenys	H x W x D	mm	230 x 840 x 840	230 x 840 x 840	285 x 840 x 840	285 x 840 x 840	285 x 840 x 840
Pakavimo matmenys	H x W x D	mm	265 x 920 x 920	265 x 920 x 920	310 x 920 x 920	310 x 920 x 920	310 x 920 x 920
Neto svoris/ Bruto svoris		kg	25,0 / 30,0	25,0 / 30,0	30,5 / 36,0	30,5 / 35,0	30,5 / 35,0
Triukšmo lygis		dB	36 / 39 / 43	36 / 41 / 45	43 / 46 / 49	45 / 52	45 / 52
Panelė	Išoriniai matmenys	mm	50 x 950 x 950	50 x 950 x 950	50 x 950 x 950	50 x 950 x 950	50 x 950 x 950
	Pakavimo matmenys	mm	105 x 1030 x 1030	105 x 1030 x 1030	105 x 1030 x 1030	105 x 1030 x 1030	105 x 1030 x 1030
	svoris, neto/bruto	kg	5,4 / 8,0	5,4 / 8,0	5,4 / 8,0	5,4 / 8,0	5,4 / 8,0
<b>Išorinis</b>							
Išoriniai matmenys	H x W x D	mm	925 x 700 x 366	958 x 843 x 392	1050 x 995 x 347	1335 x 950 x 388	1335 x 950 x 388
Pakavimo matmenys	H x W x D	mm	990 x 770 x 410	1025 x 960 x 430	1145 x 1120 x 475	1445 x 964 x 402	1445 x 964 x 402
Neto svoris/ Bruto svoris		kg	45,0 / 48,0	59,0 / 69,0	84,0 / 95,5	124,0 / 138,0	124,0 / 138,0
Triukšmo lygis		dB	52	54	55	58	58
Šaltnešio kiekis		kg	1,30	1,70	2,15	3,80	3,80
Veikimo temperatūros	šaldymo/šildymo	°C	-15~+50/ -15~+30	-15~+50/ -15~+30	-15~+50/ -15~+30	-15~+50/ -15~+30	-15~+50/ -15~+30
Vamzdelių skersmuo	dujos	mm (in)	12,7 (1/2)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)
	skystis	mm (in)	6,35 (1/4)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)
Vamzdelių maks. trasa	aukštis/ilgis	m	8 / 15	10 / 20	30 / 65	30 / 65	30 / 65
Elektros instaliacija	Maitinimo privedimas		Išorinis	Išorinis	Išorinis	Išorinis	Išorinis
	Maitinimo kabelis		3 x 2,5	3 x 2,5	3 x 4,0	5 x 2,5	5 x 2,5
	Tarpblokis k.		4 x 2,5	4 x 2,5	3 x 1,0	3 x 1,0	3 x 1,0



## KONSOLINIAI KONDICIONIERIAI

Modelis	Vidinis		RCCY18AR32	RCCY24AR32	RCCY36AR32	RCCY48AR32	RCCY60AR32
	Išorinis		RCOY18AR32	RCOY24AR32	RCOY36AR32	RCOY48FR32	RCOY60FR32
Galia	Šaldymas	kW	5,3 (2,0 - 5,6)	7,0 (3,5 - 8,0)	10,5 (6,6 - 12,8)	14,0 (7,1 - 15,6)	16,0 (7,8 - 17,5)
	Šildymas	kW	5,9 (3,0 - 6,0)	7,7 (4,5 - 8,5)	11,5 (7,4 - 13,2)	15,2 (8,0 - 17,2)	17,6 (8,5 - 19,5)
SEER/SCOP			6,1 / 4,0	6,1 / 4,0	6,1 / 4,0	6,1 / 4,0	6,1 / 4,0
Energijos klasė			A++ / A+	A++ / A+	A++ / A+	A++ / A+	A++ / A+
Maitinimo įtampa		F,V,Hz	1F,220~240V, 50Hz	1F,220~240V, 50Hz	1F,220~240V, 50Hz	3F,380~415V, 50Hz	3F,380~415V, 50Hz
El. galia	Šaldymas	kW	1,59 (0,42 - 2,10)	2,15 (0,60 - 3,00)	3,28 (1,05 - 4,66)	4,86 (1,22 - 5,70)	5,33 (1,90 - 6,70)
	Šildymas	kW	1,47 (0,50 - 1,94)	1,93 (1,10 - 2,60)	3,05 (1,10 - 4,15)	4,70 (1,20 - 5,50)	5,60 (2,00 - 6,50)
El. srovė	Šaldymas	A	2,10 - 10,10	2,50 - 13,00	14,80 (2,80 - 24,80)	14,00 (3,00 - 14,50)	16,00 (3,00 - 17,00)
	Šildymas	A	2,50 - 9,20	5,50 - 11,00	14,50 (4,20 - 21,40)	12,00 (2,00 - 14,00)	14,00 (2,00 - 16,00)
<b>Vidinis</b>							
Išoriniai matmenys	H x W x D	mm	680 x 1245 x 240	680 x 1245 x 240	680 x 1245 x 240	680 x 1670 x 245	680 x 1670 x 245
Pakavimomatmenys	H x W x D	mm	770 x 1325 x 325	770 x 1325 x 325	770 x 1325 x 325	780 x 1750 x 335	780 x 1750 x 335
Neto svoris/ Bruto svoris		kg	34,0 / 40,0	35,0 / 41,0	35,0 / 41,0	49,0 / 56,0	49,0 / 56,0
Triukšmo lygis		dB	47 / 42 / 36	49 / 46 / 43	51 / 48 / 45	52 / 45	52 / 46
<b>Išorinis</b>							
Išoriniai matmenys	H x W x D	mm	925 x 700 x 366	958 x 843 x 392	1050 x 995 x 347	1335 x 950 x 388	1335 x 950 x 388
Pakavimo matmenys	H x W x D	mm	990 x 770 x 410	1025 x 960 x 430	1145 x 1120 x 475	1445 x 964 x 402	1445 x 964 x 402
Neto svoris/ Bruto svoris		kg	45,0 / 48,0	59,0 / 69,0	84,0 / 95,5	124,0 / 138,0	124,0 / 138,0
Triukšmo lygis		dB	52	54	55	58	58
Šaltnešio kiekis		kg	1,30	1,70	2,15	3,80	3,80
Veikimo temperatūros	šaldymo/ šildymo	°C	-15~+50/ -15~+30	-15~+50/ -15~+30	-15~+50/ -15~+30	-15~+50/ -15~+30	-15~+50/ -15~+30
Vamzdelių skersmuo	dujos	mm (in)	12,7 (1/2)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)	15,88 (5/8)
	skystis	mm (in)	6,35 (1/4)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)
Vamzdelių maks. trasa	aukštis/ilgis	m	8 / 15	10 / 20	30 / 65	30 / 65	30 / 65
Elektros instaliacija	Maitinimo priedimas		Išorinis	Išorinis	Išorinis	Išorinis	Išorinis
	Maitinimo kabelis		3 x 2,5	3 x 2,5	3 x 4,0	5 x 2,5	5 x 2,5
	Tarpblokis k.		4 x 2,5	4 x 2,5	3 x 1,0	3 x 1,0	3 x 1,0